

PROBLEM SHEET - FT Tables Refresher

EE3-27: Principles of Classical and Modern Radar

Contents

1	Evaluating Functions of δ -lines	1
2	Auto-Correlation Function and PSD(f)	1
3	Transfer Function and PSD(f)	1
4	Differential Circuit	2
5	Impulse Response and PSD(f)	2
6	PSD(f) at Bandpass Filter's Output	2

1 Evaluating Functions of δ -lines

Evaluate:

(a) $-\infty \int^{\infty} (t^4 - 3t + 1) \cdot \delta(t - 2) \cdot dt$ (10%)

(b) $-\infty \int^{\infty} \{(\cos(4\pi t) * \delta(t + \frac{1}{4}))\} \cdot \delta(t - \frac{1}{8}) \cdot dt$ (10%)

(c) $\int_{-\infty}^{\infty} (t^3 - 3t^2 - 11) \cdot \delta(t - 1) \cdot dt$ (5%)

(d) $\int_{-\infty}^{\infty} \{(\sin(4\pi t) * \delta(t + \frac{1}{4}))\} \cdot \delta(t - \frac{1}{4}) \cdot dt$ (5%)

(e) $\int_{-\infty}^{\infty} (t^3 - 2t^2 + 1) \cdot \delta(t - 2) \cdot dt$ (5%)

(f) $\int_{-\infty}^{\infty} \{(\cos(2\pi t) * \delta(t - \frac{1}{4}))\} \cdot \delta(t - \frac{1}{12}) \cdot dt$ (5%)


(g) $h(3)$ where $h(t) = (t \cdot \text{rect}\{\frac{t}{8}\}) * \delta(t + 3)$ (5%)

(h) $h(3)$ where $h(t) = (t \cdot \text{rect}\{\frac{t}{8T}\}) * \delta(t - 2)$ (10%)

(i) $h(3.5)$ where $h(t) = (t \cdot \text{rect}\{\frac{t}{8T}\}) * \delta(t - 3)$ (10%)

2 Auto-Correlation Function and PSD(f)

The waveform below shows the autocorrelation function $R_{bb}(\tau)$ of what is called in communications a pseudo-random (PN) signal $b(t)$.



(a) Write a mathematical expression, using Woodward's notation, to describe the above autocorrelation function. (15%)

(b) Find the power spectral density $\text{PSD}_b(f)$ of $b(t)$. (20%)

3 Transfer Function and PSD(f)


At the input of a filter there is white Gaussian noise of power spectral density $\text{PSD}_{n_i}(f) = \frac{3}{2}10^{-6}$. If the transfer function of the filter is

$$H(f) = \Lambda \left\{ \frac{f}{10^6} \right\} \exp(-j\phi(f))$$

calculate the power of the signal at the output of the filter. (10%)

4 Differential Circuit

For the following differential circuit



find:

- (a) the impulse response and (5%)
- (b) frequency response (5%)

5 Impulse Response and PSD(f)

Consider the filter with impulse response

$$h(t) = \text{sinc}^2 \{10^6(t - 3)\}$$

and assume that the input signal $n_i(t)$ is white Gaussian noise with double-sided power spectral density $\text{PSD}_{n_i}(f) = 1.5 \times 10^{-6} \text{ W/Hz}$.

For the signal $n(t)$ at the output of the filter

- (a) find and plot its power spectral density $\text{PSD}_n(f)$; (10%)
- (b) calculate its power P_n (5%)

6 PSD(f) at Bandpass Filter's Output

Consider a bandpass filter with impulse response

$$h(t) = 8 \times 10^3 \text{sinc} \{4 \times 10^3 t\} \cdot \cos(2\pi 10^4 t)$$

and assume that at the input of this filter there is white Gaussian noise $n_i(t)$ of power spectral density $\text{PSD}_{n_i}(f) = 10^{-6}$.

For the signal $n(t)$ at the output of the filter

- (a) find and plot its power spectral density $\text{PSD}_n(f)$; (10%)
- (b) calculate its power P_n (5%)

END