

## 1 Pulse radar, round trip time

A radar sends a short pulse of microwave electromagnetic energy directed towards an aircraft at a distance  $R$ . Some of the energy scatters off of the aircraft's surface and returns to the radar after 1.3333msec. The distance  $R$  of the aircraft from the radar

- (a) 100 km
- (b) 200 km [x]
- (c) 300 km
- (d) 400 km
- (e) none of the above

## 2 Pulse radar, resolution

A radar transmits a pulse of width of  $4 \mu$  sec with pulse repetition interval  $4 m$  sec. The smallest distance between 2 targets that can resolved is

- (a) 300 m
- (b) 600 m [x]
- (c) 300 km
- (d) 600 km
- (e) none of the above

## 3 Maximum Unambiguous Range

The maximum unambiguous range that can be measured with a radar with a Pulse Repetition Frequency (PRF) of 1.5 kHz is

- (a) 50 km
- (b) 100 km [x]
- (c) 150 km
- (d) 200 km
- (e) none of the above

## 4 Linear FM CW Radar: Beat Frequency and Target Range

Consider a CW radar (Linear FM), with modulation bandwidth 32 MHz and 1 ms modulation period, operating in the presence of a target. If the beat frequency is 2MHz, the target's range is

- (a) 9.375 km [x]
- (b) 18.750 km
- (c) 28.125 km
- (d) 37.500 km
- (e) none of the above

## 5 Phased-Array Radar: ULA, Beamsteering $45^\circ$

Consider a phased-array radar that operates at a wavelength of  $\lambda = 10\text{cm}$  and employs 9 antennas in a ULA geometry with reference point (Cartesian origin) the 1st antenna and with an inter-antenna spacing  $d = 5\text{ cm}$ . If the main lobe of the array is steered towards  $\theta_{steer} = 45^\circ$ , the phase shifter of the 9th phase shifter is

- (a)  $43.1169^\circ$ ;
- (b)  $149.1169^\circ$ ;
- (c)  $210.8831^\circ$ ;
- (d)  $298.2338^\circ$ ; [x]
- (e) None of the above.